

For: Hours

Shape
Size (excl. grip)
Sensor (Eyelet) Diameter
Substrate Thickness (adapter excluded)
Total Product Surface Area
Gel Area
Adhesive Area
Integrated Lead Wire (length / color)

- Substrate Material
- Adhesive
- Gel Type
- Foam (Sponge) Material
- Release Liner
- Sensor Polymer
- Adaptor / Connector (Stud)
- Integrated Lead Wire Jacketing
- Integrated Lead Wire Cord

ACZ impedance (before defib simulation) @ 10 Hz	Ohm
DC Offset Voltage (before defib simulation)	mV
SDR Slope (remaining potential after defib) @ 30 Sec int.	mV/sec
ACZ impedance repeat (after defib simulation)	Ohm
COIIN (combined offset instability and inner noise)	µV
Bias Current Tolerance (DC offset voltage after DC loading)	mV

MR Conditional
X-ray Translucence
Integrated Abrader
Repositionability

Product Packaging Material
Resealable Pouch
Product Packaging Size (L x W)
Department Packaging - Box (L x W)
Transport Packaging - Carton (L x W)

ISO 10993
Latex Free

Halogenated Hydrocarbon Content (e.g. PVC)
Phthalate Derivatives Content (e.g. DEHP)
RoHS Compliant
REACH Compliant

Product Shelf Life (in accordance with storage guidelines)**Reorder Part Number:**